

FD514GS3-R850 C-DATA 4GE DUAL BAND WIFI6 (AX3000) XPON ONU



Kode : FD514GS3-R850

Brand : C-Data

Jenis : FTTH ONT/ONU/MDU

Harga : Rp 615.000,00

FD514GS3-R850 C-DATA is WiFi6 xPON Gateway ONT, it support 802.11a/b/g/n/ac/ax standards over 2.4GHz and 5GHz, max speed can up to 3000Mbps. FD514GS3-R850 have a high reliability and provide quality of service guarantee, easy management, flexible expansion and networking. It fully meets the ITU-T and IEEE technical standards and have good compatibility with third party OLT.

Penawaran Harga Spesial

 **08112039555**

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support MAC address learning
- Support MAC address learning account limit
- Support VLAN transparent/tag/translate/trunk
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxy mode
- Support Dynamic Bandwidth Allocation (DBA)
- Support AES encryption and decryption
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function, easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support remote WEB/Telnet access control

Specification

Model	FD514GS3-R850
User Port (LAN)	RJ-45 connector 4*10/100/1000Mbps adaptive Ethernet port Full/half duplex Auto MDI/MDI-X
Indicators	PWR / PON / LOS / LAN1-4 / INT / WIFI

PON Mode	EPON : 1000BASE-PX20+ symmetric GPON : FSAN G.984.2 standard, Class B+
PON Rate	EPON : 1.25Gbps (downstream/upstream) GPON : 2.488Gbps/1.244Gbps (downstream/upstream)
Wavelength	Transmit : 1310nm Receiver : 1490nm
Receiving sensitivity	EPON : -27dBm GPON : -28dBm
Saturated power	EPON : -3dBm GPON : -8dBm
Transmitting power	EPON : 0 ~ 4dBm GPON : 0.5 ~ 5dBm
WIFI	IEEE802.11b/g/n(2.4G) 40Mhz bandwidth maximum rate 574Mbps EIRP : 22dBm IEEE802.11a/n/ac/ax(5G) 160Mhz bandwidth maximum rate 2402Mbps EIRP : 21dBm
Power	External 12VDC/1A power supply adapter
Power consumption	<18W
Working temperature	0 to 40°C
Operating humidity	10% to 90%(Non-condensing)

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1248/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com