

# V1600D-MINI V-SOL L2 4PON EPON OLT

**Kode** : V1600D-MINI

**Brand** : V-Sol

**Jenis** : FTTH OLT

**Harga** : Rp 3.600.000,00

Rp 4.100.000,00



The V1600D-MINI vsol provide 4 GE interface for uplink, and 4 EPON ports for downstream. It can support 256 ONU under 1:64 splitter ratio. Each uplink port is connected to a EPON port directly, each PON port behaves as an independent, that EPON OLT port and there is no traffic switching between PON Ports and each PON port forwards packets to and receive packets from one dedicated uplink port.

**4\*EPON, 4GE(RJ45) Single AC Power**
**\*Sudah termasuk 4x SFP 9dBm**

Penawaran Harga Spesial

 **08112039555**

**Specification**

|                    |  |
|--------------------|--|
| <b>Model</b>       | V1600D-MINI  |
| <b>Uplink Port</b> | QTY : 4  |
|                    | RJ45(1G) : 4   |
| <b>EPON Port</b>   | QTY : 4  |
|                    | Physical Interface : SFP Slots                               |
|                    | Supported PON module level :<br>PX20, PX20+, PX20++, PX20+++ |
|                    | Max splitting ratio : 1:64                                   |

|                                   |   |
|-----------------------------------|---|
| <b>Management Port</b>            | 1*10/100 BASE-T out-band port, 1*CONSOLE port |
| <b>Backplane Bandwidth (Gbps)</b> | 16  |
| <b>Port Forwarding Rate(Mpps)</b> | 11.904  |
| <b>PON Port Specification</b>     | Transmission Distance : 20KM                  |
|                                   | EPON port speed"Symmetrical 1.25Gbps          |
|                                   | Wavelength<br>TX 1490nm<br>RX 1310nm          |
|                                   | Connector : SC/UPC                            |
|                                   | Fiber Type : 9/125µm SMF                      |
| <b>Power supply</b>               | AC:90~264V, 47/63Hz                           |
| <b>Management Mode</b>            | SNMP, Telnet and CLI                          |
| <b>Working temperature</b>        | -20 ~ +60 C                                   |
| <b>Storage temperature</b>        | -40 ~ +70 C                                   |
| <b>Relative Humidity</b>          | 5 ~ 95% (Non-condensing)                      |
| <b>Dimension (L*W*H)</b>          | 224 x 200 x 43.6 mm                           |

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1294/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**