

# Dream Machine Special Edition UNIFI UBIQUITI

**Kode** : UDM-SE

**Brand** : Ubiquiti

**Jenis** : Router Rackmount

**Harga** : Rp 9.836.000,00



**Dream Machine Special Edition** 10G Cloud Gateway with 100+ UniFi device / 1,000+ client support, 3.5 Gbps IPS routing, and built-in PoE switching.

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**



## Specification

|              |        |
|--------------|--------|
| <b>Model</b> | UDM-SE |
|--------------|--------|

|   |   |
|---|---|
| <b>Processor</b>                        | Quad-core ARM Cortex-A57 at 1.7 GHz   |
| <b>System Memory</b>                    | 4 GB  |
| <b>On-board Storage</b>                 | 16 GB eMMC<br>128 GB SSD (Integrated)   |
| <b>Ports</b>                            | 1 GbE RJ45 : 8 (1G/100M/10M)<br>2.5 GbE RJ45 : 1 (2.5G/1G/100M/10M)<br>10G SFP+ : 2 (10G/1G)    |
| <b>PoE Budget</b>                       | 180W  |
| <b>Max. PoE Wattage per Port by PSE</b> | PoE : 15.4W<br>PoE+ : 30W   |
| <b>Voltage Range PoE Mode</b>           | PoE: 44-57V<br>PoE+: 50-57V   |
| <b>Max. Power Consumption</b>           | 50W (Excluding PoE Output)  |
| <b>Form Factor</b>                      | Rack mount (1U)   |
| <b>Managed UniFi Devices</b>            | 100+  |
| <b>Managed Cameras</b>                  | (24) HD<br>(14) 2K<br>(8) 4K  |
| <b>Managed Access Hubs</b>              | 150   |
| <b>Simultaneous Users Connected</b>     | 1,000+  |
| <b>Max. WAN Port Count</b>              | 8   |
| <b>Default WAN Ports</b>                | (1) 10G SFP+<br>(1) 2.5 GbE RJ45  |
| <b>IDS/IPS Throughput</b>               | 3.5 Gbps  |
| <b>Redundancy</b>                       | Shadow Mode (VRRP) Gateway Failover<br>DC Power Backup  |
| <b>MAC Address Table Size</b>           | 4,000   |
| <b>NVR Storage</b>                      | (1) 3.5" NVR HDD bay<br>Built-in 128 GB SSD for Faster Experience                               |
| <b>Power Method</b>                     | (1) Universal AC input, 100–240V AC, 4.4A Max., 50/60 Hz<br>(1) USP-RPS DC input, 52V DC, 3.94A |
| <b>Power Supply</b>                     | AC/DC, internal, 240W   |
| <b>Supported Voltage Range</b>          | 100–240V AC   |
| <b>Dimensions (W x D x H)</b>           | 442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")  |
| <b>Enclosure Material</b>               | Aluminium CNC, SGCC steel   |
| <b>Mount Material</b>                   | SGCC steel  |

|                                      |  |
|--------------------------------------|--|
| <b>LCM Display</b>                   | 1.3" touchscreen                                   |
| <b>Management</b>                    | Ethernet<br>Bluetooth                              |
| <b>Button</b>                        | (1) Factory-reset                                  |
| <b>ESD/EMP Protection</b>            | Air: $\pm 15\text{kV}$ , contact: $\pm 8\text{kV}$ |
| <b>Ambient Operating Temperature</b> | -10 to 40° C (14 to 104° F)                        |
| <b>Ambient Operating Humidity</b>    | 5 to 95% noncondensing                             |
| <b>Certifications</b>                | CE, FCC, IC, Anatel, SRRC                          |

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1412/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**

www.citraweb.com