

# RG-RAP62-Wall RUIJIE REYEE Wi-Fi 6 AX3000 Dual-Band Multi-Port Wall-Plate AP



**Kode** : RG-RAP62-Wall

**Brand** : Ruijie - Reyee

**Jenis** : Wireless Indoor

**Ruijie Reyee RG-RAP62-Wall** Wi-Fi 6 AX3000 Dual band 2x2 MU-MIMO (2.4GHz&5GHz) wall-mount Access Point dilengkapi dengan 1x 10/100/1000Mbps WAN Port (PoE-In), 4x10/100/1000Mbps LAN Ports (1 PoE-Out) 803af PoE. Support Beamforming, Layer2/3/4 roaming, WPA2, Router mode, Captive portal, Master AP in Self-organizing Network dan Cloud/Eweb/APP management.

**\*Belum termasuk adaptor dan poe injector**

**\*Spesifikasi perangkat dijual bisa berbeda dengan yang ditampilkan karena menyesuaikan dengan regulasi di Indonesia.**

**Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.**

Penawaran Harga Spesial

 **08112039555**

- Kecepatan Wi-Fi 6 AX3000 maksimal 2401Mbps pada 5 GHz dan maksimal 573 Mbps pada 2.4 GHz
- 4 x 1GE LAN Port (LAN4 mendukung PoE Out)
- Ultra-thin design dengan ketebalan 23.5 mm (0.93 in)
- Kompatibel untuk 86-mm, EU, dan US Standard Junction Boxes
- Manajemen terpusat pada Ruijie Cloud




**Wi-Fi 6 AX3000 Speeds**  
Maximum 2401 Mbps in 5 GHz + Maximum 573 Mbps in 2.4 GHz

**Multi-Port Wall-Plate AP**  
4 x 1GE LAN ports, with LAN4 supporting PoE Out

**23.5 mm (0.93 in.) Ultra-Thin Design**  
Fit anywhere, beautify every space

**Fast and Easy Installation**  
Support 86 mm, EU, and US standard junction boxes

**Centralized Cloud Management**  
Manage the whole network on Ruijie Cloud




**Specification**

<b>Model</b>	RG-RAP62-Wall
<b>Wi-Fi Standards</b>	2.4GHz Wi-Fi 4 (IEEE 802.11b/g/n) Wi-Fi 6 (IEEE 802.11ax)  5GHz Wi-Fi 4 (IEEE 802.11a/n) Wi-Fi 5 (IEEE 802.11ac) Wi-Fi 6 (IEEE 802.11ax)
<b>Max. Transmit Power</b>	2400–2483.5 MHz, EIRP ≤27 dBm 5150–5350 MHz, EIRP ≤23 dBm 5725–5825 MHz, EIRP ≤23 dBm
<b>Max Data Rate</b>	2.4 GHz: 573 Mbps 5 GHz: 2401 Mbps
<b>Spatial Streams</b>	2.4 GHz: 2 x 2, MU-MIMO 5 GHz: 2 x 2, MU-MIMO
<b>Antennas</b>	Integrated 2.4 GHz and 5 GHz: 2 built-in omnidirectional antennas
<b>Number of 10/100/1000BASE-T ports</b>	5
<b>Power Supply</b>	PoE/PoE+
<b>PoE In standard</b>	IEEE 802.3af (PoE) Note: The standard does not support PoE Out. IEEE 802.3at (PoE+)

<b>Number of PoE Out ports</b>	1
<b>PoE budget</b>	10 W (when power source is IEEE 802.3at-compliant)
<b>Max. Power Consumption</b>	12 W (excluding PoE output)
<b>Operating temperature</b>	0°C to 40°C (32°F to 104°F)
<b>Storage temperature</b>	-40°C to +70°C (-40°F to +158°F)
<b>Operating humidity</b>	5% RH to 95% RH (non-condensing)
<b>Storage humidity</b>	5% RH to 95% RH (non-condensing)
<b>Surge protection</b>	Ethernet port: $\pm 2$ kV for common mode
<b>Mounting options</b>	Junction box
<b>MTBF</b>	400.000 hours
<b>Maximum number of clients</b>	64 (2.4 GHz) 256 (5 GHz) 256 (2.4 GHz and 5 GHz enabled)
<b>Recommended number of clients</b>	Support for IEEE 802.11ax and 160 MHz: 16 (2.4 GHz) 94 (5 GHz) 110 (2.4 GHz and 5 GHz enabled)  Support for IEEE 802.11ax and 80 MHz: 16 (2.4 GHz) 64 (5 GHz) 80 (2.4 GHz and 5 GHz enabled)  Support for IEEE 802.11ac: 8 (2.4 GHz) 32 (5 GHz) 40 (2.4 GHz and 5 GHz enabled)
<b>Maximum Number of SSIDs</b>	8
<b>AP Mesh</b>	Yes
<b>Product dimensions (W x D x H)</b>	86 mm x 23.5 mm x 125 mm (3.39 in. x 0.93 in. x 4.92 in) (excluding the mounting bracket)

[Download Datasheet](#)

\* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

**URL :** <https://www.citraweb.com/produk/1514/>

**Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email [sales@citraweb.com](mailto:sales@citraweb.com)**