

eKitEngine AR280 HUAWEI Enterprise-Grade 2.5GE Multi-Service Router

Kode : AR280

Brand : Huawei

Jenis : Router Desktop

Harga : Rp 2.105.000,00



HUAWEI eKitEngine AR280 Enterprise-Grade 2.5GE Multi-Service Router adalah Enterprise-Grade Router 2.5GE High-speed WAN Port, support up to 2000Mbps broadband dengan 4 port GE LAN support PoE+.

Produk ini merupakan produk Fix Price. Pembelian produk tidak dapat menggunakan diskon apapun.

Penawaran Harga Spesial

 **08112039555**

- Enterprise-Grade 2.5GE Multi-Service Router
- Number of IPSec Tunnels: 16
- Number of Managed APs: 16
- Number of Managed Devices: 32
- Number of connected terminals: 150
- Egress Bandwidth: 2Gbps
- VPN Forwarding Performance: 200Mbps
- 4 GE PoE+ Electrical Ports + 1 2.5GE PoE+ Electrical Port
- PoE 41W

Spesifikasi

Model	AR280
Installation type	Work bench, Against the wall
Dimensions without packaging (H x W x D) [mm(in.)]	- Basic dimensions: 35 mm x 195 mm x 130 mm (1.38 in. x 7.68 in. x 5.12 in.) - Maximum dimensions: 35 mm x 195 mm x 136 mm (1.38 in. x 7.68 in. x 5.35 in.)
Chassis height [U]	0.8
Typical power consumption [W]	5.8
Maximum power consumption [W]	49 (PoE:41W)
Power supply mode	AC power adapter
Rated input voltage [V]	100 V AC-240 V AC; 50/60 Hz
Input voltage range [V]	90 V AC-264 V AC; 45 Hz-65 Hz

Maximum output power [W]	50 W
Maximum input current [A]	0.9 A
Safety regulation certification	IEC/EN/UL 62368-1 GB 4943.1 CSA C22.2 No. 62368-1 AS/NZS 62368-1
EMC certification	EN 55032 EN 55035 EN 300386 EN 61000-3-2 EN 61000-3-3 EN 301 489-1 EN 301 489-17 ICES-003 AS/NZS CIPSR32 VCCI-CIPSR32 GB/T 9254.1 FCC CFR47 part 15
PoE	Supported
Maximum PoE output power [W]	41
PoE/PoE+ power ports	5
Long-term operating temperature [°C(°F)]	0°C to 40°C (32°F to 104°F) Note: When the altitude is 1800 m-5000 m (5906 ft.-16404.2 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH, non-condensing
Long-term operating altitude [m(ft.)]	< 5000 m (16404.2 ft.)
LAN ports	4 x GE electrical interfaces (support PoE+ 1G/100M/10M)
WAN ports	1 x 2.5GE electrical port (support PoE+ 2.5G/1G/100M/10M)
Environmental standards compliance	EN 300 019-2 IEC 60068-2
Overtemperature alarm	Supported
Certification	EMC certification Safety certification Manufacturing certification

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1553/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com